

Adaptive Policy Management (0.0.9)

License: [RUCKUS Cloud Privacy Policy](#)

Overview

The Adaptive Policy Management REST APIs and Model, allow the creation, deletion, and modification of policies, policy sets, and assigning policies to policy sets. All policies must be inherited from a policy template. Only those evaluation conditions that are defined for the template can be assigned to the policy. Once a policy is assigned to a policy set, it must be given an evaluation priority. If the priority is changed, or a policy added or removed, the priority of the other policies will be automatically re-ordered.

What This API Does

- Create, modify, and delete policies
- Manage policy sets and assignments
- Configure policy templates and evaluation conditions
- Set and manage policy priorities

Authentication

All API calls require valid authentication via Bearer token in Authorization header.

Error Handling

The API uses standard HTTP status codes with detailed error messages in the response body.

Common Error Responses

All endpoints may return these common error responses:

- **400 Bad Request:** Invalid input data or validation errors
- **401 Unauthorized:** Missing or invalid authentication
- **403 Forbidden:** Insufficient permissions
- **404 Not Found:** Requested resource doesn't exist
- **409 Conflict:** Resource conflict (e.g., duplicate names)
- **422 Unprocessable Entity:** Business rule violations
- **500 Internal Server Error:** Unexpected server errors

Policy Conditions

Manage the conditions that are applied on the specified policy.

Get Conditions

Retrieves the list of condition for the policy.

PATH PARAMETERS

templateId required	integer <int64> Template identifier.
policyId required	string <uuid> Policy identifier.

QUERY PARAMETERS

size	any Page size
page	any The page to retrieve (starts at zero).
sort	any The field name to sort, comma seperated from the sort order (asc or desc).

Responses

- > 200 Success
- > 404 Not Found

GET /policyTemplates/{templateId}/policies/{policyId}/conditions

Response samples

- 200
- 404

Content type
application/json

Copy Expand all Collapse all

```
{
  - "paging": {
    "totalCount": 0,
    "page": 0,
    "pageSize": 0,
    "pageCount": 0
  },
  - "content": [
    + { ... }
  ],
  - "_links": {
    + "property1": { ... },
    + "property2": { ... }
  }
}
```

Create Condition

Creates a condition and applies it to the policy.

PATH PARAMETERS

templateId required	integer <int64> Policy Template identifier.
policyId required	string <uuid> Policy identifier.

REQUEST BODY SCHEMA: application/json required

id	string <uuid> The identifier for this policy condition.
policyId required	string <uuid> The identifier of the policy to assign this condition.
templateAttributeId required	integer <int64> The identifier for the template attribute to associate with this condition.
templateAttribute >	object (Dynamic Policy Template Attribute) Attribute that is allowed to be assigned on a policy using the template.

evaluationRule >	object (Evaluation Criteria) Base class for evaluation criteria used in policy conditions. Supports different types of criteria including boolean, number, string regex, and date range evaluations.
_links >	object (Links)

Responses

- > 201 Condition created
- > 404 Not Found
- > 409 Condition type is already mapped.

POST /policyTemplates/{templateId}/policies/{policyId}/conditions

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "497f6eca-6276-4993-bfeb-53cbbbba6f08",
  "policyId": "2f5573e6-5ba4-48f2-a75d-df99c936463b",
  "templateAttributeId": 0,
  "templateAttribute": {
    "id": 0,
    "name": "string",
    "description": "string",
    "attributeTextMatch": "string",
    "attributeType": "STRING",
    "category": "string",
    + "_links": { ... }
  },
  "evaluationRule": {
    "criteriaType": "string",
    "booleanCriteria": true
  },
  "_links": {
    + "property1": { ... },
    + "property2": { ... }
  }
}
```

Response samples

- 201
- 404
- 409

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "497f6eca-6276-4993-bfeb-53cbbbba6f08",
  "policyId": "2f5573e6-5ba4-48f2-a75d-df99c936463b",
```

```
"templateAttributeId": 0,
- "templateAttribute": {
  "id": 0,
  "name": "string",
  "description": "string",
  "attributeTextMatch": "string",
  "attributeType": "STRING",
  "category": "string",
  + "_links": { ... }
},
- "evaluationRule": {
  "criteriaType": "string",
  "booleanCriteria": true
},
- "_links": {
  + "property1": { ... },
  + "property2": { ... }
}
}
```

Get Condition

Retrieves the requested condition for the policy.

PATH PARAMETERS

templateId required	integer <int64> Template identifier.
policyId required	string <uuid> Policy identifier.
conditionId required	string <uuid> Condition identifier.

Responses

- > 200 Success
- > 404 Not Found.

GET

/policyTemplates/{templateId}/policies/{policyId}/conditions/{conditionId}

▼

Response samples

200

404

Content type

application/json

▼

Copy

Expand all

Collapse all

```
{
  "id": "497f6eca-6276-4993-bfeb-53cbbbba6f08",
  "policyId": "2f5573e6-5ba4-48f2-a75d-df99c936463b",
  "templateAttributeId": 0,
  - "templateAttribute": {
    "id": 0,
    "name": "string",
    "description": "string",
    "attributeTextMatch": "string",
    "attributeType": "STRING",
    "category": "string",
    + "_links": { ... }
  },
  - "evaluationRule": {
    "criteriaType": "string",
    "booleanCriteria": true
  },
  - "_links": {
    + "property1": { ... },
    + "property2": { ... }
  }
}
```

Delete Conditions

Deletes the condition from the specified policy, but only if at least one condition still exists.

PATH PARAMETERS

templateId required	integer <int64> Policy Template identifier.
policyId required	string <uuid> Policy identifier.
conditionId required	string <uuid> Condition identifier.

Responses

- > **200** Condition deleted successfully.
- > **204** Condition deleted, no content.
- > **404** Policy or template not found
- > **409** Policy will not have any conditions if this is deleted.

DELETE /policyTemplates/{templateId}/policies/{policyId}/conditions/{conditionId} ▾

Response samples

200

204

404

409

Content type

application/json ▾

Copy

{ }

Update Policy Condition

Updates the policy condition from the requested values.

PATH PARAMETERS

templateId required	integer <int64>
policyId required	string <uuid>
conditionId required	string <uuid>

REQUEST BODY SCHEMA: application/json ▼
required

templateAttributeId	integer <int64> The complete template attribute to associate with this condition.
evaluationRule >	object (Evaluation Criteria) Base class for evaluation criteria used in policy conditions. Supports different types of criteria including boolean, number, string regex, and date range evaluations.

Responses

- > 200 Policy condition updated
- > 409 Invalid policy condition details provided.

PATCH /policyTemplates/{templateId}/policies/{policyId}/conditions/{conditionId} ▼

Request samples

Payload

Content type
application/json ▼

Copy Expand all Collapse all

```
{
  "templateAttributeId": 0,
  "evaluationRule": {
    "criteriaType": "string",
    "booleanCriteria": true
  }
}
```

Response samples

200 409

Content type
application/json ▼

Copy Expand all Collapse all

```
{
  "id": "40756ccc-6276-4002-b5eb-52ebbbba6508"
```

```
id": "49710eca-8276-4993-b7eb-53c0000a0108",
"policyId": "2f5573e6-5ba4-48f2-a75d-df99c936463b",
"templateAttributeId": 0,
- "templateAttribute": {
  "id": 0,
  "name": "string",
  "description": "string",
  "attributeTextMatch": "string",
  "attributeType": "STRING",
  "category": "string",
+ "_links": { ... }
},
- "evaluationRule": {
  "criteriaType": "string",
  "booleanCriteria": true
},
- "_links": {
+ "property1": { ... },
+ "property2": { ... }
}
}
```

Policy Set Assignments

Manage the assignments of policy sets to identities.

Query Policy Set Assignments

Returns the list of assignments for the specified policy set using the specified query.

PATH PARAMETERS

 policySetId required	string <uuid> Policy set identifier.
---	---

QUERY PARAMETERS

 excludeContent	boolean Default: ☐ false Indicates that the content should be excluded from the query and only count and size data returned.
--	---

REQUEST BODY SCHEMA: application/json 
required

 sortField	string The field to use to sort on.
 sortOrder	string Enum: ☐ "ASC" ☐ "DESC" Defines the sort direction for query results.
 page	integer <int32> ☐ >= 0 The page number to return, paging starts with 0.
 pageSize	integer <int32> ☐ [1 .. 2000] The number of items requested on the page.
 filters >	object The list of filters to apply.

Responses

> **200** List Policy Set Assignments in a paged format.

> **404** Policy set not found

> **422** Some of the provided query data is invalid.

POST /policySets/{policySetId}/assignments/query

Request samples

Payload

Content type

application/json

Copy Expand all Collapse all

```
{
  "sortField": "string",
  "sortOrder": "ASC",
  "page": 0,
  "pageSize": 1,
  "filters": {
    "property1": { },
    "property2": { }
  }
}
```

Response samples

200

404

422

Content type

application/json

Copy Expand all Collapse all

```
{
  "paging": {
    "totalCount": 0,
    "page": 0,
    "pageSize": 0,
    "pageCount": 0
  },
  "content": [
    + { ... }
  ],
  "_links": {
    "property1": { ... },
    "property2": { ... }
  }
}
```

Get Policy Set Assignments

Gets the list of assignments for the specified policy set.

→ policySetId required	string <uuid> Policy set identifier.
QUERY PARAMETERS	
→ size	any Page size
→ page	any The page to retrieve (starts at zero).
→ sort	any The field name to sort, comma seperated from the sort order (asc or desc).

Responses

- > 200 Policy set assignments in a paged format.
- > 404 Policy set not found

GET

/policySets/{policySetId}/assignments

▼

Response samples

200

404

Content type

application/json

▼

Copy

Expand all

Collapse all

```
{
  - "paging": {
    "totalCount": 0,
    "page": 0,
    "pageSize": 0,
    "pageCount": 0
  },
  - "content": [
    + { ... }
  ],
  - "_links": {
    + "property1": { ... },
    + "property2": { ... }
  }
}
```

Get Policy Set Assignment

Retrieves the requested policy set assignment.

PATH PARAMETERS	
→ policySetId required	string <uuid> Policy set identifier.
→ assignmentId required	string <uuid> Assignment identifier.

Responses

> 200 Policy set assignment found

> 404 Policy set or assignment not found

GET /policySets/{policySetId}/assignments/{assignmentId}

Response samples

200

404

Content type

application/json

Copy Expand all Collapse all

```
{
  "id": "497f6eca-6276-4993-bfeb-53cbbbba6f08",
  "identityId": "string",
  "identityName": "string",
  "_links": {
    + "property1": { ... },
    + "property2": { ... }
  }
}
```

Policy Templates

View the list of policy templates.

Query Template Attributes

Returns the list of attributes for the specified template using the specified query.

PATH PARAMETERS

templateId integer <int64>
required

QUERY PARAMETERS

excludeContent boolean
Default: false

REQUEST BODY SCHEMA: application/json
required

sortField	string The field to use to sort on.
sortOrder	string Enum: "ASC" "DESC" Defines the sort direction for query results.
page	integer <int32> >= 0 The page number to return, paging starts with 0.
pageSize	integer <int32> [1 .. 2000] The number of items requested on the page.
filters >	object The list of filters to apply.

Responses

- > **200** List Template Attributes in a paged format.
- > **404** Template not found
- > **422** Some of the provided query data is invalid.

POST /policyTemplates/{templateId}/attributes/query

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  "sortField": "string",
  "sortOrder": "ASC",
  "page": 0,
  "pageSize": 1,
  "filters": {
    "property1": { },
    "property2": { }
  }
}
```

Response samples

200 404 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "paging": {
    "totalCount": 0,
    "page": 0,
    "pageSize": 0,
    "pageCount": 0
  },
  "content": [
    + { ... }
  ],
  "_links": {
    + "property1": { ... },
    + "property2": { ... }
  }
}
```

Query Policy Templates

Returns the list of policy templates using the specified query.

excludeContent	boolean
	Default: false
REQUEST BODY SCHEMA: application/json	
required	
sortField	string The field to use to sort on.
sortOrder	string Enum: "ASC" "DESC" Defines the sort direction for query results.
page	integer <int32> 0 The page number to return, paging starts with 0.
pageSize	integer <int32> 1..2000 The number of items requested on the page.
filters >	object The list of filters to apply.

Responses

- > 200 List Policy Template in a paged format.
- > 422 Some of the provided query data is invalid.

POST /policyTemplates/query

Request samples

Payload

Content type

application/json

CopyExpand allCollapse all

```
{  "sortField": "string",  "sortOrder": "ASC",  "page": 0,  "pageSize": 1,  "filters": {    "property1": { },    "property2": { }  }}
```

Response samples

200422

Content type

application/json

CopyExpand allCollapse all

```
{  "paging": {    "totalCount": 0,
```

```
    "page": 0,
    "pageSize": 0,
    "pageCount": 0
  },
  - "content": [
    + { ... }
  ],
  - "_links": {
    + "property1": { ... },
    + "property2": { ... }
  }
}
```

Query Policies Across Templates

Returns the list of policies across all templates using the specified query.

QUERY PARAMETERS

 excludeContent	boolean Default: false
---	--

REQUEST BODY SCHEMA: application/json 

 sortField	string The field to use to sort on.
 sortOrder	string Enum: ASC DESC Defines the sort direction for query results.
 page	integer <int32> >= 0 The page number to return, paging starts with 0.
 pageSize	integer <int32> [1 .. 2000] The number of items requested on the page.
 filters >	object The list of filters to apply.

Responses

- > **200** List Policy in a paged format.
- > **422** Some of the provided query data is invalid.

POST /policyTemplates/policies/query 

Request samples

Payload

Content type
application/json 

Copy Expand all Collapse all

{

```
"sortField": "string",
"sortOrder": "ASC",
"page": 0,
"pageSize": 1,
- "filters": {
    "property1": { },
    "property2": { }
  }
}
```

Response samples

200

422

Content type

application/json

Copy

Expand all

Collapse all

```
{
- "paging": {
    "totalCount": 0,
    "page": 0,
    "pageSize": 0,
    "pageCount": 0
  },
- "content": [
    + { ... }
  ],
- "_links": {
    + "property1": { ... },
    + "property2": { ... }
  }
}
```

Get Policy Template

Retrieves the requested policy template.

PATH PARAMETERS

→ **templateId** required integer <int64>

Responses

> **200** Policy template found

> **404** Policy template not found

GET /policyTemplates/{templateId}

Response samples

200

404

Content type

application/json

CopyExpand allCollapse all

```
{
  "id": 0,
  "name": "string",
  "description": "string",
  "returnType": "RADIUS_ATTRIB_GROUP",
  "ruleType": "RADIUS",
  - "_links": {
    + "property1": { ... },
    + "property2": { ... }
  }
}
```

Get Template Attributes

Gets the list of attributes for the specified template.

PATH PARAMETERS	
→ templateId required	integer <int64>
QUERY PARAMETERS	
→ size	any Page size
→ page	any The page to retrieve (starts at zero).
→ sort	any The field name to sort, comma seperated from the sort order (asc or desc).
→ pageable > required	object (Pageable)

Responses

- > 200 Template attributes in a paged format.
- > 404 Template not found

GET /policyTemplates/{templateId}/attributes

Response samples

200404

Content type

application/json

CopyExpand allCollapse all

```
{
  - "paging": {
    "totalCount": 0,
    "page": 0,
    "pageSize": 0,
    "pageCount": 0
  },
  - "content": [
```

```
+ { ... }
],
- "_links": {
+ "property1": { ... },
+ "property2": { ... }
}
}
```

Get Template Attribute

Retrieves the requested template attribute.

PATH PARAMETERS

 templateId required	integer <int64>
 attributeId required	integer <int64>

Responses

> **200** Template attribute found

> **404** Template or attribute not found

GET /policyTemplates/{templateId}/attributes/{attributeId}

Response samples

200

404

Content type

application/json

Copy Expand all Collapse all

```
{
  "id": 0,
  "name": "string",
  "description": "string",
  "attributeTextMatch": "string",
  "attributeType": "STRING",
  "category": "string",
-  "_links": {
+    "property1": { ... },
+    "property2": { ... }
  }
}
```

Policies

Manages, create and get of policies assigned to a specific template.

Get Policies for Template

Gets the list of policies that are based off of this template.

PATH PARAMETERS

templateId required	integer <int64>
QUERY PARAMETERS	
size	any Page size
page	any The page to retrieve, paging starts at zero).
sort	any The field name to sort, comma seperated from the sort order (asc or desc).
pageable > required	object (Pageable)

Responses

- > 200 Policies in a paged format.
- > 400 Invalid id supplied.
- > 404 Not Found

GET /policyTemplates/{templateId}/policies

Response samples

200400404

Content type

application/json

CopyExpand allCollapse all

```
{
  - "paging": {
    "totalCount": 0,
    "page": 0,
    "pageSize": 0,
    "pageCount": 0
  },
  - "content": [
    + { ... }
  ],
  - "_links": {
    + "property1": { ... },
    + "property2": { ... }
  }
}
```

Create Policy

Creates a policy from the requested values, and based on the specified parent. If the content type of "application/ruckus.one.v1-synchronous+json" is provided, than the method will be asynchronous, and will return only once it has correctly associated with the requested radius attribute group. Otherwise it is asynchronous, and must be looked up by id to be complete.

PATH PARAMETERS	
templateId	integer <int64>

required

REQUEST BODY SCHEMA: application/json

required

id	string <uuid> The identifier for this dynamic policy.
name required	string The name of the policy.
description	string The policy description.
policyType required	string Enum: "RADIUS" "DPSK" The data type for this attribute text. EX: it identifies which type of value the test data will be. This cannot be changed, and will be matched with the policy template for this policy type. It cannot be changed.
onMatchResponse	string The response details if the policy is matched. For policy types which are RADIUS and DPSK, this is expected to be the identifier of a valid RADIUS attribute group.
policySetCount	integer <int64> The number of policy sets that this policy is assigned to.
conditionsCount	integer <int64> The number of conditions that are used when evaluating this policy.
policySetNames	Array of strings The names of the policy sets that this policy is currently assigned to.
_links >	object (Links)

Responses

- > 201 Created
- > 202 Accepted
- > 409 Invalid policy details provided.

POST /policyTemplates/{templateId}/policies

Request samples

Payload

Content type

application/json

Copy Expand all Collapse all

```
{
  "id": "497f6eca-6276-4993-bfeb-53cbbbba6f08",
  "name": "string",
  "description": "string",
  "policyType": "RADIUS",
  "onMatchResponse": "string",
  "policySetCount": 0,
  "conditionsCount": 0,
  "policySetNames": [
    "string"
  ]
}
```

```
      "string"
    },
    - "_links": {
      + "property1": { ... },
      + "property2": { ... }
    }
  }
}
```

Response samples

- 201
- 202
- 409

Content type

application/ruckus.one.v1-synchronous+json

Copy Expand all Collapse all

```
{
  "id": "497f6eca-6276-4993-bfeb-53cbbbba6f08",
  "name": "string",
  "description": "string",
  "policyType": "RADIUS",
  "onMatchResponse": "string",
  "policySetCount": 0,
  "conditionsCount": 0,
  - "policySetNames": [
    "string"
  ],
  - "_links": {
    + "property1": { ... },
    + "property2": { ... }
  }
}
```

Query Policies for Template

Returns the list of policies which are based on the provided template using the specified query details.

PATH PARAMETERS

templateId required	integer <int64>
---	-----------------

QUERY PARAMETERS

excludeContent	boolean
	Default: false

REQUEST BODY SCHEMA: application/json

required

sortField	string	The field to use to sort on.
sortOrder	string	Enum: "ASC" "DESC" Defines the sort direction for query results.
page	integer <int32>	>= 0 The page number to return, paging starts with 0.
pageSize	integer <int32>	[1 .. 2000] The number of items requested on the page.

Responses

- > 200 List Policy in a paged format.
- > 400 Invalid id supplied.
- > 404 Not Found
- > 422 Some of the provided query data is invalid.

POST /policyTemplates/{templateId}/policies/query

Request samples

Payload

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "sortField": "string",
  "sortOrder": "ASC",
  "page": 0,
  "pageSize": 1,
  "filters": {
    "property1": { },
    "property2": { }
  }
}
```

Response samples

200 400 404 422

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "paging": {
    "totalCount": 0,
    "page": 0,
    "pageSize": 0,
    "pageCount": 0
  },
  "content": [
    + { ... }
  ],
  "_links": {
    + "property1": { ... },
    + "property2": { ... }
  }
}
```

Get Policy

Retrieves the requested policy.

PATH PARAMETERS

templateId required	integer <int64>
policyId required	string <uuid>

Responses

- > 200 Policy success
- > 400 Invalid id supplied.
- > 404 Policy Template not found.

GET

/policyTemplates/{templateId}/policies/{policyId}

▼

Response samples

200

400

404

Content type

application/json

▼

Copy

Expand all

Collapse all

```
{
  "id": "497f6eca-6276-4993-bfeb-53cbbbba6f08",
  "name": "string",
  "description": "string",
  "policyType": "RADIUS",
  "onMatchResponse": "string",
  "policySetCount": 0,
  "conditionsCount": 0,
  "policySetNames": [
    "string"
  ],
  "_links": {
    "property1": { ... },
    "property2": { ... }
  }
}
```

Delete Policy

Deletes the policy and conditions, may not be assigned to a service.

PATH PARAMETERS

templateId required	integer <int64>
policyId	string <uuid>

required

Responses

- > **200** Policy deleted
- > **204** Policy deleted, no content.
- > **404** Policy not found
- > **409** The requested policy is still in use in a policy set.

DELETE /policyTemplates/{templateId}/policies/{policyId}

Response samples

- 200
- 204
- 404
- 409

Content type
application/json

Copy

{ }

Update Policy

Updates the policy from the requested values. The policy template assigned to this policy cannot be changed.

PATH PARAMETERS

templateId required	integer <int64>
policyId required	string <uuid>

REQUEST BODY SCHEMA: application/json
required

name required	string The name of the policy. Must be unique within the tenant.
description	string The policy description.
onMatchResponse	string The response details if the policy is matched. For policy types which are RADIUS and DPSK, this is expected to be the identifier of a valid RADIUS attribute group.

Responses

- > **200** Policy updated
- > **409** Invalid policy details provided.

PATCH /policyTemplates/{templateId}/policies/{policyId}

Request samples

Payload

Content type

application/json

Copy

```
{
  "name": "string",
  "description": "string",
  "onMatchResponse": "string"
}
```

Response samples

200

409

Content type

application/json

Copy Expand all Collapse all

```
{
  "id": "497f6eca-6276-4993-bfeb-53cbbbba6f08",
  "name": "string",
  "description": "string",
  "policyType": "RADIUS",
  "onMatchResponse": "string",
  "policySetCount": 0,
  "conditionsCount": 0,
  - "policySetNames": [
    "string"
  ],
  - "_links": {
    + "property1": { ... },
    + "property2": { ... }
  }
}
```

Prioritized Policies

Manage the prioritized policies within a policy set.

Get Prioritized Policy

Retrieves the requested prioritized policy.

PATH PARAMETERS

policySetId required	string <uuid> Policy set identifier.
policyId required	string <uuid> Policy identifier.

Responses

> 200 Prioritized policy found

> **404** Policy set or policy not found

GET /policySets/{policySetId}/prioritizedPolicies/{policyId}

Response samples

200

404

Content type

application/json

Copy Expand all Collapse all

```
{
  "policyId": "2f5573e6-5ba4-48f2-a75d-df99c936463b",
  "priority": 0,
  "_links": {
    + "property1": { ... },
    + "property2": { ... }
  }
}
```

Assign Policy to Policy Set

Assigns a policy to a policy set with a specific priority.

PATH PARAMETERS

policySetId required	string <uuid> Policy set identifier.
policyId required	string <uuid> Policy identifier.

REQUEST BODY SCHEMA: application/json required

policyId	string <uuid> The identifier for the prioritized policy. Will be ignored on a put, as URL is the identifier.
priority	integer <int32> The priority of this policy, 1 being the highest priority.
_links >	object (Links)

Responses

> **201** Policy assigned to policy set

> **409** Invalid assignment details provided.

PUT /policySets/{policySetId}/prioritizedPolicies/{policyId}

Request samples

Payload

Content type

application/json

CopyExpand allCollapse all

```
{
  "policyId": "2f5573e6-5ba4-48f2-a75d-df99c936463b",
  "priority": 0,
  "_links": {
    + "property1": { ... },
    + "property2": { ... }
  }
}
```

Response samples

- 201
- 409

Content type
application/json

CopyExpand allCollapse all

```
{
  "policyId": "2f5573e6-5ba4-48f2-a75d-df99c936463b",
  "priority": 0,
  "_links": {
    + "property1": { ... },
    + "property2": { ... }
  }
}
```

Remove Policy from Policy Set

Removes a policy from a policy set.

PATH PARAMETERS

policySetId required	string <uuid> Policy set identifier.
policyId required	string <uuid> Policy identifier.

Responses

- > 200 Policy removed from policy set successfully.
- > 204 Policy removed from policy set, no content.
- > 404 Policy set or policy not found

DELETE /policySets/{policySetId}/prioritizedPolicies/{policyId}

Response samples

200204404

Content type
application/json

Copy

{ }

Get Prioritized Policies

Gets the list of prioritized policies for the specified policy set.

PATH PARAMETERS

 policySetId	string <uuid>
required	Policy set identifier.

Responses

> **200** Prioritized policies in a paged format.

> **404** Policy set not found

GET /policySets/{policySetId}/prioritizedPolicies

Response samples

200

404

Content type

application/json

Copy Expand all Collapse all

```
{
  - "paging": {
    "totalCount": 0,
    "page": 0,
    "pageSize": 0,
    "pageCount": 0
  },
  - "content": [
    + { ... }
  ],
  - "_links": {
    + "property1": { ... },
    + "property2": { ... }
  }
}
```

Policy Sets

Manages the policy sets.

Create Policy Set

Creates a policy set from the requested values.

REQUEST BODY SCHEMA: application/json required

id	string <uuid> The identifier for this dynamic policy.
name required	string The policy set name.
description required	string The policy set description.
mappedPolicyCount	integer <int64> The number of policies mapped to this policy set.
assignmentCount	integer <int64> The number of assignments to this policy set.
policyNames	Array of strings The names of the policies mapped to this policy set.
externalAssignments >	Array of objects (Policy Set Assignment Groups) The list of external assignments assigned to this policy set.
policyOverrideEnabled	boolean The policy override enabled flag.
_links >	object (Links)

Responses

- > 201 Policy set created
- > 409 Invalid policy set details provided.

POST /policySets

Request samples

Payload

Content type
application/json

CopyExpand allCollapse all

```
{
  "id": "497f6eca-6276-4993-bfeb-53cbbbba6f08",
  "name": "string",
  "description": "string",
  "mappedPolicyCount": 0,
  "assignmentCount": 0,
  "policyNames": [
    "string"
  ],
  "externalAssignments": [
    + { ... }
  ],
  "policyOverrideEnabled": true,
  "_links": {
    + "property1": { ... },
    + "property2": { ... }
  }
}
```

Response samples

201

409

Content type

application/json

Copy Expand all Collapse all

```
{
  "id": "497f6eca-6276-4993-bfeb-53cbbbba6f08",
  "name": "string",
  "description": "string",
  "mappedPolicyCount": 0,
  "assignmentCount": 0,
  - "policyNames": [
    "string"
  ],
  - "externalAssignments": [
    + { ... }
  ],
  "policyOverrideEnabled": true,
  - "_links": {
    + "property1": { ... },
    + "property2": { ... }
  }
}
```

Query Policy Sets

Returns the list of policy sets using the specified query.

QUERY PARAMETERS

→ excludeContent

boolean

Default: false

REQUEST BODY SCHEMA: application/json ▼

required

→ sortField	string	The field to use to sort on.
→ sortOrder	string	Enum: "ASC" "DESC" Defines the sort direction for query results.
→ page	integer <int32> ≥ 0	The page number to return, paging starts with 0.
→ pageSize	integer <int32> [1 .. 2000]	The number of items requested on the page.
→ filters >	object	The list of filters to apply.

Responses

> 200 List Policy Sets in a paged format.

> **422** Some of the provided query data is invalid.

POST /policySets/query

Request samples

Payload

Content type

application/json

Copy Expand all Collapse all

```
{
  "sortField": "string",
  "sortOrder": "ASC",
  "page": 0,
  "pageSize": 1,
  "filters": {
    "property1": { },
    "property2": { }
  }
}
```

Response samples

200

422

Content type

application/json

Copy Expand all Collapse all

```
{
  "paging": {
    "totalCount": 0,
    "page": 0,
    "pageSize": 0,
    "pageCount": 0
  },
  "content": [
    + { ... }
  ],
  "_links": {
    + "property1": { ... },
    + "property2": { ... }
  }
}
```

Get Policy Set

Retrieves the requested policy set.

PATH PARAMETERS

 **policySetId**
required

string <uuid>
Policy set identifier.

Responses

> **200** Policy set found

> **404** Policy set not found

GET /policySets/{policySetId}

Response samples

200

404

Content type

application/json

Copy Expand all Collapse all

```
{
  "id": "497f6eca-6276-4993-bfeb-53cbbbba6f08",
  "name": "string",
  "description": "string",
  "mappedPolicyCount": 0,
  "assignmentCount": 0,
  - "policyNames": [
    "string"
  ],
  - "externalAssignments": [
    + { ... }
  ],
  "policyOverrideEnabled": true,
  - "_links": {
    + "property1": { ... },
    + "property2": { ... }
  }
}
```

Delete Policy Set

Deletes the policy set, may not be assigned to a service.

PATH PARAMETERS

policySetId
required

string <uuid>
Policy set identifier.

Responses

> **200** Policy set deleted

> **204** Policy set deleted, no content.

> **404** Policy set not found

> **409** The requested policy set is still in use.

DELETE /policySets/{policySetId}

Response samples

200

204

404

409

Content type

application/json

Copy

{ }

Update Policy Set

Updates the policy set from the requested values.

PATH PARAMETERS

policySetId required	string <uuid> Policy set identifier.
--	--

REQUEST BODY SCHEMA: application/json

required

id	string <uuid> The identifier for this dynamic policy.
name required	string The policy set name.
description required	string The policy set description.
mappedPolicyCount	integer <int64> The number of policies mapped to this policy set.
assignmentCount	integer <int64> The number of assignments to this policy set.
policyNames	Array of strings The names of the policies mapped to this policy set.
externalAssignments >	Array of objects (Policy Set Assignment Groups) The list of external assignments assigned to this policy set.
policyOverrideEnabled	boolean The policy override enabled flag.
_links >	object (Links)

Responses

- > 200 Policy set updated
- > 409 Invalid policy set details provided.

PATCH /policySets/{policySetId}

Request samples

Payload

Content type

application/json

CopyExpand allCollapse all

```
{
  "id": "497f6eca-6276-4993-bfeb-53cbbbba6f08",
  "name": "string",
  "description": "string",
  "mappedPolicyCount": 0,
  "assignmentCount": 0,
- "policyNames": [
    "string"
  ],
- "externalAssignments": [
  + { ... }
],
  "policyOverrideEnabled": true,
- "_links": {
  + "property1": { ... },
  + "property2": { ... }
}
}
```

Response samples

200

409

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "id": "497f6eca-6276-4993-bfeb-53cbbbba6f08",
  "name": "string",
  "description": "string",
  "mappedPolicyCount": 0,
  "assignmentCount": 0,
- "policyNames": [
    "string"
  ],
- "externalAssignments": [
  + { ... }
],
  "policyOverrideEnabled": true,
- "_links": {
  + "property1": { ... },
  + "property2": { ... }
}
}
```