

Tenant Management API (v0.3.0)

[Ruckus Network Technical Documents](#)

Overview

This document provides information about Tenant management.

Rate Limit

For the Ptenant REST API the following will be true:

- Limits are applied to each tenant.
- A maximum of 200 calls can be made per second.
- Each second 100 calls will be returned to be used.

Notification Recipient

Manage notification recipients.

Query Notification Recipients

Query notification recipient list.

REQUEST BODY SCHEMA: application/json

	required
page	integer <int32>
pageSize	integer <int32>
sortField	string Enum: "name" "email" "mobile"
sortOrder	string Enum: "ASC" "DESC"
searchTargetFields	Array of strings Items Enum: "name" "email" "mobile"
searchString	string
filters >	object

Responses

> 202 Accepted
> 400 Bad/Malformed Request
> 415 Unsupported Media Type
> 500 Internal Server Error

POST

/tenants/notifications/recipients/query

▼

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  "page": 0,
  "pageSize": 0,
  "sortField": "name",
  "sortOrder": "ASC",
  - "searchTargetFields": [
    "name"
  ],
  "searchString": "string",
  - "filters": {
    "property1": { },
    "property2": { }
  }
}
```

Response samples

202

400

500

Content type
application/vnd.ruckus.v1+json

Copy Expand all Collapse all

```
{
  "totalPages": 0,
  "totalElements": 0,
  "size": 0,
  - "content": [
    { }
  ],
  "number": 0,
  - "sort": {
    "empty": true,
    "sorted": true,
    "unsorted": true
  },
  - "pageable": {
    "offset": 0,
    + "sort": { ... },
    "pageNumber": 0,
    "pageSize": 0,
    "paged": true,
    "unpaged": true
  },
  "first": true,
  "last": true,
  "numberOfElements": 0,
  "empty": true
}
```

Get Notification Recipients

Get notification recipient list.

Responses

- > 200 OK
- > 415 Unsupported Media Type

GET /tenants/notificationRecipients

Response samples

200

Content type

application/vnd.ruckus.v1+json

CopyExpand allCollapse all

```
[
  - {
    "id": "string",
    "description": "string",
    + "endpoints": [ ... ],
    "emailPreferences": true,
    "smsPreferences": true,
    "privilegeGroupId": "string",
    "recipientType": "string"
  }
]
```

Add Notification Recipient

Add notification recipient.

REQUEST BODY SCHEMA: application/json

required

id	string
description	string
endpoints >	Array of objects (NotificationEndpointDTO)
emailPreferences	boolean
smsPreferences	boolean
privilegeGroupId	string
recipientType	string

Responses

- > 202 Accepted
- > 400 Bad/Malformed Request
- > 415 Unsupported Media Type
- > 500 Internal Server Error

Request samples

Payload

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "id": "string",
  "description": "string",
  "endpoints": [
    + { ... }
  ],
  "emailPreferences": true,
  "smsPreferences": true,
  "privilegeGroupId": "string",
  "recipientType": "string"
}
```

Response samples

202

400

500

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "requestId": "string",
  "response": {
    "id": "string",
    "description": "string",
    + "endpoints": [ ... ],
    "emailPreferences": true,
    "smsPreferences": true,
    "privilegeGroupId": "string",
    "recipientType": "string"
  }
}
```

Delete Notification Recipient

Delete notification recipient list.

REQUEST BODY SCHEMA: application/vnd.ruckus.v1+json ▼

required

Array [

id	string
description required	string
emailPreferences	boolean

└─ smsPreferences	boolean
└─ privilegeGroup >	object (PrivilegeGroup)
└─ endpoints >	Array of EmailNotificationEndpoint (object) or MobilePushNotificationEndpoint (object) or SmsNotificationEndpoint (object)

Responses

- > 202 Accepted
- > 415 Unsupported Media Type
- > 500 Internal Server Error

DELETE

/tenants/notificationRecipients

Request samples

Payload

Content type

application/vnd.ruckus.v1+json

Copy

Expand all

Collapse all

```
[  
  - {  
    "id": "string",  
    "description": "string",  
    "emailPreferences": true,  
    "smsPreferences": true,  
    + "privilegeGroup": { ... },  
    + "endpoints": [ ... ]  
  }  
]
```

Response samples

202

500

Content type

application/vnd.ruckus.v1+json

Copy

Expand all

Collapse all

```
{  
  "requestId": "string",  
  "response": { }  
}
```

Tenant

Manage tenants.

Get Tenant

Get tenant by identifier.

QUERY PARAMETERS

 deep	boolean
---	---------

Responses

- > 200 OK
- > 415 Unsupported Media Type

GET /tenants/self

▼

Response samples

200

Content type

application/vnd.ruckus.v1+json

▼

Copy Expand all Collapse all

```
{
  "id": "string",
  "createdDate": "2019-08-24T14:15:22Z",
  "updatedAt": "2019-08-24T14:15:22Z",
  "entitlementId": "string",
  "externalModifiedDate": "2019-08-24T14:15:22Z",
  "maintenanceState": true,
  "maintenanceDate": "2019-08-24T14:15:22Z",
  "name": "string",
  "externalId": "string",
  - "admins": [
    + { ... }
  ],
  - "notificationRecipients": [
    + { ... }
  ],
  - "authentications": [
    + { ... }
  ],
  "almActivated": true,
  "almActivationDate": "2019-08-24T14:15:22Z",
  "almSysAccountId": "string",
  "almMigrationFlag": true,
  "almMigrationDate": "2019-08-24T14:15:22Z",
  "accountTier": "string",
  "accountVertical": "string",
  "obsolete": true,
  "oemName": "string",
  "upgradeGroup": "string",
  - "msp": {
    "mspLabel": "string",
    "mspFQDN": "string",
    "logoUUID": "string",
    "alarmNotificationLogoUUID": "string",
```

```

    "pingNotificationLogoUUID": "string",
    "mlisaLogoUUID": "string",
    "pingLoginLogoUUID": "string",
    "defaultLogoUUID": "string",
    "contactSupportUrl": "string",
    "contractSupportBehavior": "string",
    "openCaseUrl": "string",
    "openCaseBehavior": "string",
    "myOpenCaseUrl": "string",
    "myOpenCaseBehavior": "string",
    "changePasswordUrl": "string",
    "phone": "string",
    "email": "string",
    "website": "string",
    "isDisableNotification": true
  },
  - "MspEcServiceDates": {
    "parentMspId": "string",
    "serviceExpirationDate": "2019-08-24T14:15:22Z",
    "serviceEffectiveDate": "2019-08-24T14:15:22Z"
  },
  - "tenantMFA": {
    "mfaStatus": "string",
    "recoveryCodes": "string"
  },
  "serviceAccount": true,
  "mspPingOrgId": "string",
  "aggregateNotifications": true,
  "excludeecforAggregation": true,
  "pingMigrated": true,
  "inMaintenance": true,
  - "account": {
    "id": "string",
    "createdDate": "2019-08-24T14:15:22Z",
    "updatedAt": "2019-08-24T14:15:22Z",
    "streetAddress": "string",
    "state": "string",
    "country": "string",
    "postalCode": "string",
    "phoneNumber": "string",
    "faxNumber": "string",
    "city": "string",
    "type": "string",
    "mappingURL": "string",
    "latitude": 0.1,
    "longitude": 0.1,
    "parentId": "string"
  },
  "extendedTrial": true,
  "propertyCode": "string",
  "expirationEnforcement": true,
  "expirationEnforcementDate": "2019-08-24T14:15:22Z",
  "preferences": "string",
  "isActivated": true,
  "ruckusUser": true,
  - "delegationsTo": [
    + { ... }
  ],
  "parentId": "string",
  "status": "active",
  "tenantType": "REC",
  "subscribes": "string"

```

Update a Tenant

Update tenant information are tenant name, tenant type,external id by passing the alto tenant id.

REQUEST BODY SCHEMA: application/vnd.ruckus.v1+json ▼
required

newIdmId	string
var	boolean
tenantName	string
enableMfa	string
enableSa	boolean
enableBeta	boolean
enableAlpha	boolean
entitlementId	string
subscribes	string
requestId	string
response	string
userName	string
missingAdminIds	Array of strings

Responses

> **200** OK

> **415** Unsupported Media Type

PUT /tenants/self ▼

Request samples

Payload

Content type

application/vnd.ruckus.v1+json

Copy

Expand all

Collapse all

```
{
  "newIdmId": "string",
  "var": true,
  "tenantName": "string",
  "enableMfa": "string",
  "enableSa": true,
  "enableBeta": true,
  "enableAlpha": true,
  "entitlementId": "string",
  "subscribes": "string",
  "requestId": "string",
  "response": "string",
  "userName": "string",
  "missingAdminIds": Array of strings
}
```



```
"subscribes": "string",
"requestId": "string",
"response": "string",
"userName": "string",
- "missingAdminIds": [
  "string"
]
}
```

Response samples

200

Content type

application/vnd.ruckus.v1+json

Copy

```
{
  "requestId": "string"
}
```

Get Beta Feature Identifiers

Get list of beta features.

Responses

> 200 OK

> 415 Unsupported Media Type

GET /tenants/betaFeatures



Response samples

200

Content type

application/json

Copy

Expand all

Collapse all

```
{
- "betaFeatures": [
  + { ... }
],
"errorMessage": "string",
- "invalidFeatureIds": [
  "string"
]
}
```

Update Beta Feature Identifiers

Update beta feature identifiers.

REQUEST BODY SCHEMA: application/json

required

betaFeatureIds

Array of strings

unique

Responses

- > 200 OK
- > 415 Unsupported Media Type

PUT /tenants/betaFeatures

Request samples

Payload

Content type

application/json

Copy Expand all Collapse all

{
 - "betaFeatureIds": [
 "string"
]
}

Response samples

200

Content type

application/json

Copy Expand all Collapse all

{
 - "betaFeatures": [
 + { ... }
],
 "errorMessage": "string",
 - "invalidFeatureIds": [
 "string"
]
}

Delegation

Manage delegations.

Get Delegation

Get delegation by ID.

PATH PARAMETERS

delegationId

required

string

Responses

- > 200 OK
- > 415 Unsupported Media Type

GET

/tenants/delegations/{delegationId}

▼

Response samples

200

Content type

application/vnd.ruckus.v1+json

▼

Copy

```
{
  "id": "string",
  "createdDate": "2019-08-24T14:15:22Z",
  "updatedDate": "2019-08-24T14:15:22Z",
  "delegatedTo": "string",
  "type": "VAR",
  "status": "INVITED",
  "delegatedBy": "string",
  "expiryDate": "2019-08-24T14:15:22Z",
  "delegatedToName": "string",
  "delegatedToAdmin": "string",
  "parentId": "string",
  "isValid": true
}
```

Respond to Delegation

A VAR uses this endpoint to respond to a delegation invitation; the response is either accept or reject.

PATH PARAMETERS

—

—

delegationId

required

string

REQUEST BODY SCHEMA:

application/vnd.ruckus.v1+json

▼

required

—

—

accept

required

boolean

—

fromTenantId

required

string

Responses

- > 202 Accepted
- > 415 Unsupported Media Type
- > 500 Internal Server Error

PUT

/tenants/delegations/{delegationId}

▼

Request samples

Payload

Content type
application/vnd.ruckus.v1+json

Copy

```
{
  "accept": true,
  "fromTenantId": "string"
}
```

Response samples

202 500

Content type
application/vnd.ruckus.v1+json

Copy Expand all Collapse all

```
{
  "requestId": "string",
  "response": {
    "id": "string",
    "createdDate": "2019-08-24T14:15:22Z",
    "updatedAt": "2019-08-24T14:15:22Z",
    "delegatedTo": "string",
    "type": "VAR",
    "status": "INVITED",
    "delegatedBy": "string",
    "expiryDate": "2019-08-24T14:15:22Z",
    "delegatedToName": "string",
    "delegatedToAdmin": "string",
    "parentId": "string",
    "isValid": true
  }
}
```

Revoke VAR Delegation

Revoke VAR delegation by ID.

PATH PARAMETERS

delegationId
required string

Responses

> 202 Accepted

> **415** Unsupported Media Type

> **500** Internal Server Error

DELETE /tenants/delegations/{delegationId}



Response samples

202

500

Content type

application/vnd.ruckus.v1+json



Copy

Expand all

Collapse all

```
{
  "requestId": "string",
  "response": { }
}
```

Grant Access

Grant Ruckus customer support access to my account.

Responses

> **202** Accepted

> **415** Unsupported Media Type

> **500** Internal Server Error

POST /tenants/supportDelegations



Response samples

202

500

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "requestId": "string",
  "response": {
    "id": "string",
    "createdDate": "2019-08-24T14:15:22Z",
    "updatedAt": "2019-08-24T14:15:22Z",
    "delegatedTo": "string",
    "type": "VAR",
    "status": "INVITED",
    "delegatedBy": "string",
    "expiryDate": "2019-08-24T14:15:22Z",
    "delegatedToName": "string",
    "delegatedToAdmin": "string",
    "parentId": "string",
    "isValid": true
  }
}
```

Revoke Access

Revoke Ruckus customer support's access to my account.

Responses

- > 202 Accepted
- > 415 Unsupported Media Type
- > 500 Internal Server Error

DELETE /tenants/supportDelegations

Response samples

202500

Content type
application/json

CopyExpand allCollapse all

```
{  "requestId": "string",  "response": { }}
```

Get Delegations

Get delegation list.

QUERY PARAMETERS

type

stringEnum: "VAR" "SUPPORT" "MSP" "SUPPORT_EC" "MSP_INSTALLER" "MSP_INTEGRATOR" "UNKNOWN"

Responses

- > 200 OK
- > 415 Unsupported Media Type

GET /tenants/delegations

Response samples

200

Content type
application/vnd.ruckus.v1+json

CopyExpand allCollapse all

```
[
```

```
- {
  "id": "string",
  "createdDate": "2019-08-24T14:15:22Z",
  "updatedDate": "2019-08-24T14:15:22Z",
  "delegatedTo": "string",
  "type": "VAR",
  "status": "INVITED",
  "delegatedBy": "string",
  "expiryDate": "2019-08-24T14:15:22Z",
  "delegatedToName": "string",
  "delegatedToAdmin": "string",
  "parentId": "string",
  "isValid": true
}
```

Invite VAR

Send invitation to VAR (aka delegate) to manage my account.This operation is not supported using client credentials.

REQUEST BODY SCHEMA: application/vnd.ruckus.v1+json 

required

 username

Responses

> **202** Accepted

> **400** Bad/Malformed Request

> **404** Requested Resource or Related-Entity Not Found

> **415** Unsupported Media Type

> **500** Internal Server Error

POST /tenants/delegations 

Request samples

Payload

Content type

application/vnd.ruckus.v1+json 

Copy

```
{
  "username": "string"
}
```

Response samples

202

400

404

500

Content type

application/vnd.ruckus.v1+json 

Copy Expand all Collapse all

```
{
  "requestId": "string",
  "response": {
    "id": "string",
    "createdDate": "2019-08-24T14:15:22Z",
    "updatedAt": "2019-08-24T14:15:22Z",
    "delegatedTo": "string",
    "type": "VAR",
    "status": "INVITED",
    "delegatedBy": "string",
    "expiryDate": "2019-08-24T14:15:22Z",
    "delegatedToName": "string",
    "delegatedToAdmin": "string",
    "parentId": "string",
    "isValid": true
  }
}
```

User Profile

Manage user profiles.

Get User Profile

Get user profile.

Responses

> **200** OK

> **415** Unsupported Media Type

GET /tenants/userProfiles



Response samples

200

Content type

application/vnd.ruckus.v1+json



Copy Expand all Collapse all

```
{
  "region": "string",
  "allowedRegions": [
    + { ... }
  ],
  "externalId": "string",
  "pver": "string",
  "companyName": "string",
  "delegatedDogfood": true,
  "firstName": "string",
  "lastName": "string",
  "username": "string",
  "role": "string",
  "roles": [
    "string"
  ]
}
```



```
    },
    "detailLevel": "ba",
    "dateFormat": "mm/dd/yyyy",
    "newDateFormat": "string",
    "email": "string",
    "var": true,
    "tenantId": "string",
    "varTenantId": "string",
    "adminId": "string",
    "support": true,
    "dogfood": true,
    "edgeBeta": "string",
    "alphaStatus": "string",
    "phoneNumber": "string",
    "customRoleName": "string",
    "customRoleType": "string",
    "privilegeGroupName": "string",
    "privilegeGroupType": "string",
    - "scopes": [
        "string"
    ],
    "preferredLanguage": "string",
    - "preferredNotifications": {
        "emailPreferences": true,
        "smsPreferences": true
    }
}
```

Update User Profile

Update user profile.

REQUEST BODY SCHEMA: application/vnd.ruckus.v1+json 

required

 region	string
 allowedRegions >	Array of objects (Region) unique Regions are the continents to which the user is allowed. Currently permitted regions are North America, European Union and Asia.
 externalId	string
 companyName	string
 delegatedDogfood	boolean Delegation to a dog food account (internal RUCKUS test accounts, named per the saying, eat your own dog food).
 firstName	string
 lastName	string
 username	string
 role	string Deprecated
 roles	Array of strings unique
 detailLevel required	string Enum: "ba" "it" "su" "debug"

dateFormat	string
required	Enum: "mm/dd/yyyy" "dd/mm/yyyy" "yyyy/mm/dd"
newDateFormat	string
email	string
var	boolean
tenantId	string
varTenantId	string
adminId	string
edgeBeta	string
alphaStatus	string
phoneNumber	string
customRoleName	string
customRoleType	string
privilegeGroupName	string
privilegeGroupType	string
scopes	Array of strings unique
preferredLanguage	string
preferredNotifications	object (PreferredNotifications)

Responses

- > 200 Accepted
- > 415 Unsupported Media Type
- > 500 Internal Server Error

PUT /tenants/userProfiles

Request samples

Payload

Content type
application/vnd.ruckus.v1+json

Copy Expand all Collapse all

```
{
  "region": "string",
  "allowedRegions": [
    + { ... }
  ],
  "externalId": "string",
  "companyName": "string",
  "delegatedDogfood": true,
  "firstName": "string",
```

```

    "lastName": "string",
    "username": "string",
    "role": "string",
  - "roles": [
      "string"
    ],
    "detailLevel": "ba",
    "dateFormat": "mm/dd/yyyy",
    "newDateFormat": "string",
    "email": "string",
    "var": true,
    "tenantId": "string",
    "varTenantId": "string",
    "adminId": "string",
    "edgeBeta": "string",
    "alphaStatus": "string",
    "phoneNumber": "string",
    "customRoleName": "string",
    "customRoleType": "string",
    "privilegeGroupName": "string",
    "privilegeGroupType": "string",
  - "scopes": [
      "string"
    ],
    "preferredLanguage": "string",
  - "preferredNotifications": {
      "emailPreferences": true,
      "smsPreferences": true
    }
}

```

Response samples

200

500

Content type

application/vnd.ruckus.v1+json

Copy Expand all Collapse all

```

{
  "requestId": "string",
  - "response": {
      "region": "string",
    + "allowedRegions": [ ... ],
      "externalId": "string",
      "pver": "string",
      "companyName": "string",
      "delegatedDogfood": true,
      "firstName": "string",
      "lastName": "string",
      "username": "string",
      "role": "string",
    + "roles": [ ... ],
      "detailLevel": "ba",
      "dateFormat": "mm/dd/yyyy",
      "newDateFormat": "string",
      "email": "string",
      "var": true,
      "tenantId": "string",
      "varTenantId": "string",
      "adminId": "string"
    }
}

```

```
    "adminId": "string",
    "support": true,
    "dogfood": true,
    "edgeBeta": "string",
    "alphaStatus": "string",
    "phoneNumber": "string",
    "customRoleName": "string",
    "customRoleType": "string",
    "privilegeGroupName": "string",
    "privilegeGroupType": "string",
+   "scopes": [ ... ],
    "preferredLanguage": "string",
+   "preferredNotifications": { ... }
  }
}
```

Get Account

Get account details.

Responses

> **200** OK

> **415** Unsupported Media Type

GET /tenants/accounts



Response samples

200

Content type

application/json

Copy

```
{
  "organization": "string",
  "address": "string",
  "city": "string",
  "stateOrProvince": "string",
  "zip": "string",
  "country": "string"
}
```

Privacy Features

Manage privacy features.

Get Configured Privacy Settings

Get configured privacy settings.

QUERY PARAMETERS

id

string

Responses

- > 200 OK
- > 415 Unsupported Media Type

GET /tenants/privacySettings

Response samples

200

Content type

application/vnd.ruckus.v1+json

Copy Expand all Collapse all

```
{
  - "privacyFeatures": [
    + { ... }
  ]
}
```

Clear and Save Privacy Settings

Clear and save privacy settings.

REQUEST BODY SCHEMA: application/json

required

privacyFeatures >

Array of objects (PrivacyFeature) [1 .. 2147483647] items unique

Manage privacy settings, including arc and related features.

Responses

- > 200 OK
- > 415 Unsupported Media Type

POST /tenants/privacySettings

Request samples

Payload

Content type

application/json

Copy Expand all Collapse all

```
{
  - "privacyFeatures": [
    + { ... }
  ]
}
```

Response samples

200

Content type

application/vnd.ruckus.v1+json

CopyExpand allCollapse all

```
{
  - "privacyFeatures": [
    + { ... }
  ]
}
```

Add or Update Privacy Settings

Configure, add, or update tenant-specific privacy settings such as arc, visibility controls, and related features.

REQUEST BODY SCHEMA: application/json

required

privacyFeatures >

Array of objects (PrivacyFeature) [1 .. 2147483647] itemsunique

Manage privacy settings, including arc and related features.

Responses

> 200 OK

> 415 Unsupported Media Type

PATCH /tenants/privacySettings

Request samples

Payload

Content type

application/json

CopyExpand allCollapse all

```
{
  - "privacyFeatures": [
    + { ... }
  ]
}
```

Response samples

200

Content type

application/vnd.ruckus.v1+json

CopyExpand allCollapse all

```
{
  - "privacyFeatures": [
    + { ... }
  ]
}
```

Administrator

Manage administrators.

Get Administrator

Get list of administrators.

QUERY PARAMETERS

withExternalId	boolean
Default:	false

Responses

- > 200 OK
- > 415 Unsupported Media Type

GET /admins

Response samples

200

Content type
application/vnd.ruckus.v1+json

Copy Expand all Collapse all

```
[
  {
    "id": "string",
    "externalId": "string",
    "email": "string",
    "name": "string",
    "lastName": "string",
    "phoneNumber": "string",
    "role": "string",
    "delegateToAllECs": true,
    "delegatedECs": [ ... ],
    "detailLevel": "ba",
    "authenticationId": "string"
  }
]
```

Update Administrator

Update administrator.

QUERY PARAMETERS

updateSwuId	boolean
Default:	false

REQUEST BODY SCHEMA: application/vnd.ruckus.v1+json required

id	string
----	--------

externalId	string										
email required	string										
name	string										
lastName	string										
phoneNumber	string										
role required	string										
delegateToAllECs	boolean If set to true, this admin is permitted to manage all delegated account IDs (RECs or MSP-ECs).										
delegatedECs	Array of strings List of delegated account IDs (RECs or MSP-ECs) that this admin is permitted to manage.										
detailLevel	string Enum: "ba" "it" "su" "debug" <table><thead><tr><th>Enum</th><th>Meaning</th></tr></thead><tbody><tr><td>ba</td><td>Show events appropriate for a basic user.</td></tr><tr><td>it</td><td>Show events appropriate for someone having training as an IT administrator.</td></tr><tr><td>su</td><td>Show events appropriate for a super user.</td></tr><tr><td>debug</td><td>Show events useful for debugging purposes.</td></tr></tbody></table>	Enum	Meaning	ba	Show events appropriate for a basic user.	it	Show events appropriate for someone having training as an IT administrator.	su	Show events appropriate for a super user.	debug	Show events useful for debugging purposes.
Enum	Meaning										
ba	Show events appropriate for a basic user.										
it	Show events appropriate for someone having training as an IT administrator.										
su	Show events appropriate for a super user.										
debug	Show events useful for debugging purposes.										
authenticationId	string										

Responses

- > 202 Accepted
- > 415 Unsupported Media Type
- > 500 Internal Server Error

PUT /admins

Request samples

Payload

Content type
application/vnd.ruckus.v1+json

Copy Expand all Collapse all

```
{
  "id": "string",
  "externalId": "string",
  "email": "string",
  "name": "string",
  "lastName": "string",
  "phoneNumber": "string",
  "role": "string",
  "delegateToAllECs": true,
  "delegatedECs": [
```



```
    "string"
  ],
  "detailLevel": "ba",
  "authenticationId": "string"
}
```

Response samples

- 202
- 500

Content type

application/vnd.ruckus.v1+json

Copy Expand all Collapse all

```
{
  "requestId": "string",
  "response": {
    "id": "string",
    "createdDate": "2019-08-24T14:15:22Z",
    "updatedAt": "2019-08-24T14:15:22Z",
    "detailLevel": "ba",
    "externalId": "string",
    + "adminRoles": [ ... ],
    + "adminAppSettings": [ ... ],
    "dateFormat": "mm/dd/yyyy",
    "username": "string",
    + "authentication": { ... },
    "firstName": "string",
    "lastName": "string",
    "phoneNumber": "string",
    "local": true,
    "defaultTenant": "string",
    "parentId": "string"
  }
}
```

Add Administrator

Add administrator.

REQUEST BODY SCHEMA: application/vnd.ruckus.v1+json ▼
required

id	string
externalId	string
email required	string
name	string
lastName	string
phoneNumber	string
role required	string
delegateToALLECs	boolean If set to true, this admin is permitted to manage all delegated account IDs (RECs or MSP-ECs).

delegatedECs	Array of strings List of delegated account IDs (RECs or MSP-ECs) that this admin is permitted to manage.										
detailLevel	string Enum: "ba" "it" "su" "debug" <table><thead><tr><th>Enum</th><th>Meaning</th></tr></thead><tbody><tr><td>ba</td><td>Show events appropriate for a basic user.</td></tr><tr><td>it</td><td>Show events appropriate for someone having training as an IT administrator.</td></tr><tr><td>su</td><td>Show events appropriate for a super user.</td></tr><tr><td>debug</td><td>Show events useful for debugging purposes.</td></tr></tbody></table>	Enum	Meaning	ba	Show events appropriate for a basic user.	it	Show events appropriate for someone having training as an IT administrator.	su	Show events appropriate for a super user.	debug	Show events useful for debugging purposes.
Enum	Meaning										
ba	Show events appropriate for a basic user.										
it	Show events appropriate for someone having training as an IT administrator.										
su	Show events appropriate for a super user.										
debug	Show events useful for debugging purposes.										
authenticationId	string										

Responses

- > 202 Accepted
- > 400 Bad/Malformed Request
- > 415 Unsupported Media Type
- > 500 Internal Server Error

POST /admins

Request samples

Payload

Content type

application/vnd.ruckus.v1+json

Copy

Expand all

Collapse all

```
{
  "id": "string",
  "externalId": "string",
  "email": "string",
  "name": "string",
  "lastName": "string",
  "phoneNumber": "string",
  "role": "string",
  "delegateToAllECs": true,
  "delegatedECs": [
    "string"
  ],
  "detailLevel": "ba",
  "authenticationId": "string"
}
```

Response samples

202

400

500

Content type

application/vnd.ruckus.v1+json

application/vnd.ruckus.v1+json

Copy

Expand all

Collapse all

```
{
  "requestId": "string",
  "response": {
    "id": "string",
    "createdDate": "2019-08-24T14:15:22Z",
    "updatedAt": "2019-08-24T14:15:22Z",
    "detailLevel": "ba",
    "externalId": "string",
    + "adminRoles": [ ... ],
    + "adminAppSettings": [ ... ],
    "dateFormat": "mm/dd/yyyy",
    "username": "string",
    + "authentication": { ... },
    "firstName": "string",
    "lastName": "string",
    "phoneNumber": "string",
    "local": true,
    "defaultTenant": "string",
    "parentId": "string"
  }
}
```

Delete Administrators

Delete administrators in bulk.

REQUEST BODY SCHEMA: application/vnd.ruckus.v1+json ▾

required

Array [
 string
]

Responses

> **202** Accepted

> **415** Unsupported Media Type

> **500** Internal Server Error

DELETE /admins



Request samples

Payload

Content type

application/vnd.ruckus.v1+json

Copy

```
[
  "string"
]
```

Response samples

202

500

Content type

application/vnd.ruckus.v1+json

Copy Expand all Collapse all

```
{
  "requestId": "string",
  "response": { }
}
```

Get Administrator

Get list of administrators.

QUERY PARAMETERS

withExternalId boolean
Default: false

REQUEST BODY SCHEMA: application/json
required

page	integer <int32>
pageSize	integer <int32>
sortField	string Enum: "name" "username" "role" "authenticationType"
sortOrder	string Enum: "ASC" "DESC"
searchTargetFields	Array of strings Items Enum: "name" "username"
searchString	string
filters >	object

Responses

> 200 OK

> 415 Unsupported Media Type

POST /admins/query

Request samples

Payload

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "page": 0,
  "pageSize": 0,
  "sortField": "name",
  "sortOrder": "ASC",
  - "searchTargetFields": [
    "name"
  ],
  "searchString": "string",
  - "filters": {
    "property1": { },
    "property2": { }
  }
}
```

Response samples

200

Content type

application/vnd.ruckus.v1+json

Copy

Expand all

Collapse all

```
{
  "totalPages": 0,
  "totalElements": 0,
  "size": 0,
  - "content": [
    { }
  ],
  "number": 0,
  - "sort": {
    "empty": true,
    "sorted": true,
    "unsorted": true
  },
  - "pageable": {
    "offset": 0,
    + "sort": { ... },
    "pageNumber": 0,
    "pageSize": 0,
    "paged": true,
    "unpaged": true
  },
  "first": true,
  "last": true,
  "numberOfElements": 0,
  "empty": true
}
```

Get Administrator

Get administrator by identifier.

PATH PARAMETERS

 adminId required	string
--	--------

Responses

- > 200 OK
- > 415 Unsupported Media Type

GET /admins/{adminId}

▼

Response samples

200

Content type
application/vnd.ruckus.v1+json

Copy Expand all Collapse all

```
{
  "id": "string",
  "externalId": "string",
  "email": "string",
  "name": "string",
  "lastName": "string",
  "phoneNumber": "string",
  "role": "string",
  "delegateToAllECs": true,
  "delegatedECs": [
    "string"
  ],
  "detailLevel": "ba",
  "authenticationId": "string"
}
```

Delete Administrator

Delete administrator by identifier.

PATH PARAMETERS

 adminId required	string
--	--------

Responses

- > 202 Accepted
- > 415 Unsupported Media Type
-

> 500 Internal Server Error

DELETE /admins/{adminId}

Response samples

202

500

Content type

application/vnd.ruckus.v1+json

Copy Expand all Collapse all

```
{
  "requestId": "string",
  "response": { }
}
```

acx-mobile-push-notification-endpoint-controller

Add Mobile Push Notification

Add mobile push notification.

QUERY PARAMETERS

app string

REQUEST BODY SCHEMA: application/vnd.ruckus.v1+json

required

id

string

destination
required

string
The email address to which notifications are sent.

active

boolean

status

string
Enum: "OK" "BOUNCED"
This parameter is set to bounced when emails are not deliverable to the destination.

type

string
EmailNotificationEndpoint

Responses

> 200 OK

> 415 Unsupported Media Type

POST /tenants/mobilePushNotifications

Request samples

Payload

Content type

application/vnd.ruckus.v1+json

Example

Example
EmailNotificationEndpoint

Copy

```
{
  "id": "string",
  "destination": "string",
  "active": true,
  "status": "OK",
  "type": "EmailNotificationEndpoint"
}
```

Response samples

200

Content type
application/vnd.ruckus.v1+json

Copy Expand all Collapse all

```
{
  "requestId": "string",
  "response": {
    "id": "string",
    "createdDate": "2019-08-24T14:15:22Z",
    "updatedAt": "2019-08-24T14:15:22Z",
    "destination": "string",
    "active": true,
    "status": "OK",
    "type": "string",
    "parentId": "string",
    "platform": "string",
    "deviceToken": "string",
    "deviceId": "string"
  }
}
```

authentication-controller

Get Authentications

Get all authentications.

QUERY PARAMETERS

withExtendedRole boolean
Default: false

Responses

> 200 OK

> 415 Unsupported Media Type

GET /tenants/authentications

Response samples

Content type

application/vnd.ruckus.v1+json

Copy

Expand all

Collapse all

```
[
  - {
    "id": "string",
    "clientID": "string",
    "clientSecret": "string",
    "scopes": "string",
    "tokenURL": "string",
    "authorizationURL": "string",
    "authenticationType": "IDM",
    "samlFileURL": "string",
    "name": "string",
    "clientIDStatus": "ACTIVE",
    "samlFileType": "DIRECT_URL",
    + "domains": [ ... ],
    "samlSignatureEnabled": true,
    "samlEncryptionCertificateId": "string",
    "parentTenantId": "string",
    "samlEncryptionPublicCertificate": "string",
    "samlEncryptionPrivateKey": "string"
  }
]
```

Add Authentication

Add authentication.

REQUEST BODY SCHEMA: application/vnd.ruckus.v1+json

required

id	string
clientID	string
clientSecret	string
scopes	string
tokenURL	string
authorizationURL	string
authenticationType	string Enum: "IDM" "SAML" "OATH2_OIDC" "OAUTH2_CLIENT_CREDENTIALS" "LDAP" "GOOGLE_WORKSPACE"
samlFileURL	string
name	string
clientIDStatus	string Enum: "ACTIVE" "REVOKED"
samlFileType	string Enum: "DIRECT_URL" "FILE"
domains	Array of strings

samlSignatureEnabled	boolean
samlEncryptionCertificateId	string
parentTenantId	string
samlEncryptionPublicCertificate	string
samlEncryptionPrivateKey	string

Responses

- > 200 OK
- > 415 Unsupported Media Type

POST /tenants/authentications

Request samples

Payload

Content type

application/vnd.ruckus.v1+json

CopyExpand allCollapse all

```
{
  "id": "string",
  "clientId": "string",
  "clientSecret": "string",
  "scopes": "string",
  "tokenURL": "string",
  "authorizationURL": "string",
  "authenticationType": "IDM",
  "samlFileURL": "string",
  "name": "string",
  "clientIdStatus": "ACTIVE",
  "samlFileType": "DIRECT_URL",
  "domains": [
    "string"
  ],
  "samlSignatureEnabled": true,
  "samlEncryptionCertificateId": "string",
  "parentTenantId": "string",
  "samlEncryptionPublicCertificate": "string",
  "samlEncryptionPrivateKey": "string"
}
```

Response samples

200

Content type

application/vnd.ruckus.v1+json

CopyExpand allCollapse all

```
{
  "id": "string",
  "clientId": "string",
  "clientSecret": "string",
  "scopes": "string",
  "tokenURL": "string",
  "authorizationURL": "string",
  "authenticationType": "IDM",
  "samlFileURL": "string",
  "name": "string",
  "clientIdStatus": "ACTIVE",
  "samlFileType": "DIRECT_URL",
  "domains": [
    "string"
  ],
  "samlSignatureEnabled": true,
  "samlEncryptionCertificateId": "string",
  "parentTenantId": "string",
  "samlEncryptionPublicCertificate": "string",
  "samlEncryptionPrivateKey": "string"
}
```

```
"clientId": "string",
"clientSecret": "string",
"scopes": "string",
"tokenURL": "string",
"authorizationURL": "string",
"authenticationType": "IDM",
"samlFileURL": "string",
"name": "string",
"clientIdStatus": "ACTIVE",
"samlFileType": "DIRECT_URL",
- "domains": [
    "string"
],
"samlSignatureEnabled": true,
"samlEncryptionCertificateId": "string",
"parentTenantId": "string",
"samlEncryptionPublicCertificate": "string",
"samlEncryptionPrivateKey": "string"
}
```