

Guest API and Model Documentation (1.7.1)

License: [RUCKUS Cloud Privacy Policy](#)

<https://support.ruckuswireless.com/ruckus-cloud-wifi-legal-terms-and-conditions>

Overview

Rate Limit

For the ApOps REST API the following will be true:

- Limits are applied to each tenant.
- A maximum of 200 calls can be made per second.
- Each second 100 calls will be returned to be used.

Portal Service Profile

Manage Portal Service Profile.

Get Portal Service Profiles Deprecated

Get portal service profile for the list.

QUERY PARAMETERS

serviceName	string Portal Service Profile Name
networkId	string NetworkId
tags	string Tags
page	integer <int32> Default: 1 Indicates the page to return, will be 1 based, and default to page 1
pageSize	integer <int32> Default: 256 Default is 256, indicates the page size to return
excludeContent	boolean Default: false Get the total count information from the query and NOT pull the data

Responses

> 200 OK

> 400 Bad/malformed request

> 401 Not-authorized

> 403 Forbidden

> **404** Requested resource or related-entity not found

> **422** Validation error

> **423** Locked

> **500** Internal Server Error

GET /portalServiceProfiles

Response samples

200

400

401

403

404

422

423

500

Content type

application/json

Copy Expand all Collapse all

```
{
  - "content": [
    + { ... }
  ],
  - "paging": {
    "page": 0,
    "pageSize": 0,
    "totalCount": 0
  }
}
```

Remove Portal Service Profile Deprecated

Remove portal service profile by ids.

REQUEST BODY SCHEMA: application/json

required

Array [
 string
]

Responses

> **202** Accepted

> **400** Bad/malformed request

> **401** Not-authorized

> **403** Forbidden

> **404** Requested resource or related-entity not found

> **422** Validation error

> **423** Locked

> **500** Internal Server Error

DELETE /portalServiceProfiles

Request samples

Payload

Content type
application/json

Copy

```
[  
  "string"  
]
```

Response samples

202

400

401

403

404

422

423

500

Content type
application/json

Copy Expand all Collapse all

```
{  
  "requestId": "string",  
  "response": { }  
}
```

Get Tags Filter of Portal Service Profiles **Deprecated**

Get tags filter for portal service profile lists.

Responses

> **200** OK

> **400** Bad/malformed request

> **401** Not-authorized

> **403** Forbidden

> **404** Requested resource or related-entity not found

> **422** Validation error

> **423** Locked

> **500** Internal Server Error

GET /portalServiceProfiles/tags

Response samples

200

400

401

403

404

422

423

500

Content type

application/json

Copy

Expand all

Collapse all

```
[
  - {
    "id": "string",
    "name": "string",
    "tags": "string"
  }
]
```

Get Network Filter of Portal Service Profiles Deprecated

Get network filter for portal service profile lists.

Responses

> 200 OK

> 400 Bad/malformed request

> 401 Not-authorized

> 403 Forbidden

> 404 Requested resource or related-entity not found

> 422 Validation error

> 423 Locked

> 500 Internal Server Error

GET /portalServiceProfiles/networks

Response samples

200

400

401

403

404

422

423

500

Content type

application/json

Copy

Expand all

Collapse all

```
[
  - {
    "id": "string",
    "name": "string",
```

```
    "tags": "string"
  }
}
```

Guest User

Manage guest users.

Import Guest Users by Network ID Deprecated

Import one or more guest pass users from the payload's CSV file.

PATH PARAMETERS

→ **networkId** required string
Network ID of the guest network to which the guest user will connect.

QUERY PARAMETERS

→ **expiration.activationType** required string
Enum: "Creation" "Login"
When activation type is set to creation, the guest pass is valid when it's created until the specified expiration duration, even if it's not being used; when set to login, the guest pass is valid starting from when the user first logs on until the specified expiration duration.

→ **expiration.duration** required integer <int32> [1 .. 8760]

→ **expiration.unit** required string
Enum: "Minute" "Hour" "Day" "Week" "Month" "Year" "Never"

→ **maxDevices** required integer <int32>
Default: 3
Maximum number of devices the guest user can simultaneously connect to the guest network. If set to -1, no limit is enforced.

→ **deliveryMethods**
Array of strings unique
Items Enum: "MAIL" "SMS" "WHATSAPP" "STUB" "PRINT"
At least one delivery method.

REQUEST BODY SCHEMA: multipart/form-data
required

→ **file** required string <binary>

Responses

> **201** Created

> **400** Bad/malformed request

> **401** Not-authorized

> **403** Forbidden

> **404** Requested resource or related-entity not found

> **422** Validation error

> **423** Locked

> **500** Internal Server Error

POST /networks/{networkId}/guestUsers

Response samples

201

400

401

403

404

422

423

500

Content type

application/json

Copy Expand all Collapse all

```
{
  "requestId": "string",
  "response": {
    "downloadUrl": "string",
    "data": [ ... ]
  }
}
```

Get Guest Users **Deprecated**

Get user details for the list of provisioned guest users.

QUERY PARAMETERS

page	integer <int32> Page index
size	integer <int32> The size of the page to be returned

Responses

> **200** OK

> **400** Bad/malformed request

> **401** Not-authorized

> **403** Forbidden

> **404** Requested resource or related-entity not found

> **422** Validation error

> **423** Locked

> **500** Internal Server Error

GET /guestUsers

Response samples

200

400

401

403

404

422

423

500

Content type

application/json

Copy Expand all Collapse all

```
{
  "content": [
    + { ... }
  ],
  "totalElements": 0
}
```

Add Guest Users **Deprecated**

Provision one or more guest users as defined in the payload.

REQUEST BODY SCHEMA: application/json

required

Array [

name

required

string

The name assigned to the guest user.

disabled

boolean

If true, this guest user will not be permitted to join the guest network.

networkId

required

string

Network ID of the guest network.

notes

string [0 .. 180] characters

email

string

mobilePhoneNumber

required

string

The mobile phone number associated to the guest user.

maxDevices

required

integer <int32>

Maximum number of devices the guest user can simultaneously connect to the guest network. If set to minus one, no limit is enforced.

deliveryMethods

required

Array of strings unique

Items Enum: "MAIL" "SMS" "WHATSAPP" "STUB" "PRINT"

At least one delivery method.

expiration >

required

object (GuestUserExpiration)

]

Responses

> **201** Created

> **400** Bad/malformed request

> **401** Not-authorized

> **403** Forbidden

> **404** Requested resource or related-entity not found

> **422** Validation error

> **423** Locked

> **500** Internal Server Error

POST /guestUsers

Request samples

Payload

Content type

application/json

Copy Expand all Collapse all

```
[
  - {
    "name": "string",
    "disabled": false,
    "networkId": "string",
    "notes": "string",
    "email": "string",
    "mobilePhoneNumber": "string",
    "maxDevices": 3,
    + "deliveryMethods": [ ... ],
    + "expiration": { ... }
  }
]
```

Response samples

201

400

401

403

404

422

423

500

Content type

application/json

Copy Expand all Collapse all

```
{
  "requestId": "string",
  - "response": [
    + { ... }
  ]
}
```

Delete Guest Users **Summary**

Delete Guest Users Deprecated

Delete one or more guest users per their IDs as defined in the payload.

REQUEST BODY SCHEMA: `application/json`
required

```
Array [  
  string  
]
```

Responses

> **200** OK

> **400** Bad/malformed request

> **401** Not-authorized

> **403** Forbidden

> **404** Requested resource or related-entity not found

> **422** Validation error

> **423** Locked

> **500** Internal Server Error

DELETE `/guestUsers`

Request samples

Payload

Content type
`application/json`

Copy

```
[  
  "string"  
]
```

Response samples

200

400

401

403

404

422

423

500

Content type
`application/json`

Copy Expand all Collapse all

```
{  
  "requestId": "string",  
  "response": { }  
}
```

Get Guest User by ID Deprecated

Get a guest user.

PATH PARAMETERS

→ **guestUserId** string
required

Responses

> **200** OK

> **400** Bad/malformed request

> **401** Not-authorized

> **403** Forbidden

> **404** Requested resource or related-entity not found

> **422** Validation error

> **423** Locked

> **500** Internal Server Error

GET /guestUsers/{guestUserId} ▾

Response samples

200

400

401

403

404

422

423

500

Content type

application/json

Copy Expand all Collapse all

```
{
  "id": "string",
  "createdDate": 0,
  "lastModified": 0,
  "name": "string",
  "disabled": false,
  "networkId": "string",
  "notes": "string",
  "email": "string",
  "mobilePhoneNumber": "string",
  "maxDevices": 3,
  "macAddresses": [
    "string"
  ],
  "ssid": "string",
  "deliveryMethods": [
```

```
    "MAIL"
  },
  "guestUserType": "GuestPass",
  "expiration": {
    "activationType": "Creation",
    "duration": 0,
    "unit": "Minute"
  },
  "password": "string",
  "expirationDate": 0
}
```

Delete Guest User by ID Deprecated

Delete a guest user.

PATH PARAMETERS

 <code>guestUserId</code> required	<code>string</code>
---	---------------------

Responses

> **200** OK

> **400** Bad/malformed request

> **401** Not-authorized

> **403** Forbidden

> **404** Requested resource or related-entity not found

> **422** Validation error

> **423** Locked

> **500** Internal Server Error

DELETE `/guestUsers/{guestUserId}`

Response samples

200

400

401

403

404

422

423

500

Content type

application/json

Copy Expand all Collapse all

```
{
  "requestId": "string",
  "response": { }
}
```

Update Guest User Deprecated

Update guest user enable/disable status or create new password for the guest user.

PATH PARAMETERS

→ **guestUserId** string
required

REQUEST BODY SCHEMA: application/json
required

Parameter combination option:

Option1: Enable or disable user by "action: enabled" or "action: disabled".

Option2: Regenerate guest user credential by "action: regenerate" + "deliveryMethods"

→ **action** string
required
Action for updating guest user.

→ **deliveryMethods** Array of strings **unique**
Items Enum: "MAIL" "SMS" "WHATSAPP" "STUB" "PRINT"
At least one delivery method.

Responses

> **200** OK

> **400** Bad/malformed request

> **401** Not-authorized

> **403** Forbidden

> **404** Requested resource or related-entity not found

> **422** Validation error

> **423** Locked

> **500** Internal Server Error

PATCH /guestUsers/{guestUserId}

Request samples

Payload

Content type
application/json

Copy

```
{  
  "action": "enabled",  
  "deliveryMethods": "MAIL"  
}
```

Response samples

200

400

401

403

404

422

423

500

Content type

application/json

Copy Expand all Collapse all

```
{
  "requestId": "string",
  "response": {
    "id": "string",
    "createdDate": 0,
    "lastModified": 0,
    "name": "string",
    "disabled": false,
    "networkId": "string",
    "notes": "string",
    "email": "string",
    "mobilePhoneNumber": "string",
    "maxDevices": 3,
    "macAddresses": [ ... ],
    "ssid": "string",
    "deliveryMethods": [ ... ],
    "guestUserType": "GuestPass",
    "expiration": { ... },
    "password": "string",
    "expirationDate": 0
  }
}
```